

Low Profile Lift Table HY SERIES

HY Series

- ▲ Heavy duty design with larger platform
- ▲ These tables achieve a low closed height, eliminating the need for a pit installation.
- ▲ They are manufactured to all European safety standards including EN1570:1999.
- ▲ Remote power pack with pedestal and controls, IP54 protection.
- ▲ Upper platform fitted with safety perimeter to prevent descent on contact with obstructions.
- ▲ 24V control box with UP and DOWN buttons and emergency stop.
- ▲ External power pack equipped with a relief valve against overloading and a compensated flow valve for controlling lowering speed. Power supply are AC 380V/50HZ/3phase.
- ▲ Hose burst safety valve to stop the lift table lowering in case of hose breakage.
- ▲ Removable lifting eyes to facilitate handling and installation of the lift table.
- ▲ Oil-less bushings on pivot points.
- ▲ Loading ramp is a standard equipment.



i-Lift No.	1312801	1312802	1312803	1312804	1312805	1312806	1312807	1312808	1312809	1312810
Model	HY1001	HY1002	HY1003	HY1004	HY1005	HY1501	HY1502	HY1503	HY2001	HY2002
Capacity (kg)			1000				1500			2000
Platform Size LXW(mm)	1450×1140	1600×1140	1450×800	1600×800	1600×1000	1600×800	1600×1000	1600×1200	1600×1200	1600×1000
Min. Height (mm)			85					105		
Max. Height (mm)			860					870		
Stroke (mm)						775				
Lifting Time (second)			25				30		35	
Power Pack			380V/50HZ,AC 0.75kw				380V/50HZ,AC 1.5kw		380V/50HZ,AC 2.2kw	
Net Weight (kg)	357	364	326	332	352	367	401	415	419	405

"RCV HANDLING MACHINERY" :: HHF 037A, Industrial Estate, BBG 3000, HAL-FAR, Malta

Tel: +356 2148 5681 :: Fax: +356 2144 1747 :: Mob: +356 9905 4096

Vat Nr. MT1467-3111

email: info@rcvmalta.com :: Web: rcvmalta.com